














# GLOBAL ACCESS SYSTEMS

## PHOTO ELECTRIC BEAMS

ITEM		PRODUCT	PRODUCT DESCRIPTION
			<b>Photo Electric</b>
PH FAAC		Photo Electric	Self aligning wall mounted photocells. Rated Range 20m.
ASS FP PWB		Stand Plate Bracket	OPTIONS: Aluminium support stand. Foundation plate for support stand. Adjustable pivoting wall bracket.
PH FAACW		Photo Electric	<b>WIRELESS</b> Self aligning wall mounted photocells. Rated Range 20m.
ASS FP PWB		Stand Plate Bracket	OPTIONS: Aluminium support stand. Foundation plate for support stand. Adjustable pivoting wall bracket.
XP 15B		Photo Electric	Photo electric safety beams. Transmitter receiver type. "Bus" connection. Rated Range 15m.
ASS FP PWB		Stand Plate Bracket	OPTIONS: Aluminium support stand. Foundation plate for support stand. Adjustable pivoting wall bracket.
PBEAM		Photo Electric	Wall mounted photo beam. Rated to 30metres. Adjustable.
		Column	OPTIONS: Pedestal for the installation of photo electric.
FSWITCH		Photo Electric	Flush mounted photocell. Rated to 30 metres.
MB		Box	OPTIONS: Metal box to be welded
EDGE		Edge Sensor	Wireless safety edge. Modulated infra-red safety device, powered by lithium batteries. Includes edge strip & fixed receiver.
RH WS ASS		Receiver housing Wall Support Support stand	OPTIONS: Aluminium edge counter-contact profile 2.5m for housing the fixed receiver. Adjustable wall support for receiver.  Aluminium support stand (stand alone column)with foundation plate, for receiver installation.
PH ST		Photo Electric	12/24 Volt Photo Electric Beam. Range 20m. 180deg horizontal & 5deg vertical direction angle.